

Description

Composite hose made from polypropylene fabrics and films with an abrasion resistant PVC coated fabric cover, reinforced with internal and external wire helixes. The hose contains a barrier layer for 100% aromatic hydrocarbons.

Principal Applications

Transfuel is a suction and discharge hose mainly for the transfer of petroleum products by road, rail tankers and loading gantries. It is not advisable to use this hose with aviation fuels due to possible contamination from zinc flakes.



Construction

Inner wire : Galvanised zinc coated mild steel
Lining : Polypropylene Fabric
Outer cover : PVC Coated Terylene Weave Fabric
Colour Code : Green / Blue outer cover with white stripe
Outer Wire : Galvanised zinc coated mild steel

Physical Properties

Max. Elongation : 10% on proof pressure
Maximum Twist : 10° /mtr
Vacuum range : 0.9 bar
Electrical resistance : 2.5 Ohms/mtr < 2" Hose
 1.0 Ohms/mtr > 2" Hose

Standards

Manufactured to the specifications where applicable to EN 13765 Type 2

Temperature

Depending on the conveyant -30°C to +80°C

Special application

Transfuel can be supplied with Stainless Steel outer wire also. This hose is called **Transfuel-S**

Specifications

Bore diameter		Bend radius		Max work. pressure		Weight / meter		Maximum length	
mm	inch	Mm	inch	psi	bar	Lbs/Ft	kg/m	meter	Feet
25	1	50	2.0	100	7	0.67	1.00	30	100
38	1.5	75	2.9	100	7	0.94	1.40	30	100
50	2	80	3.1	100	7	1.04	1.55	30	100
65	2.5	90	3.5	100	7	1.61	2.40	30	100
75	3	125	4.9	100	7	1.98	2.95	30	100
100	4	220	8.6	100	7	2.62	3.90	30	100

Minimum Burst Pressure: 4 times Working Pressure (safety factor 4:1)

NOTE: This information is for guidance only, dimensions and weights shown are approximate.
 We reserve the right to alter or amend specifications as deemed necessary.

RADCOFLEX® reserves the right to change product specifications without notice.
 RADCOFLEX® Trade Mark of RADCOFLEX India (P) Ltd.

