

Transoil / Transoil S composite hose

description

Composite hose made from polypropylene fabrics and films with an abrasion resistant PVC coated fabric cover. Inner and outer wires are galvanized mild steel.

classification

Fuel and Oil Group 1 Hose.

colour code

Available in several colors – Please specify at time of ordering.

principal applications

Transoil is especially suitable for transfer of petroleum products in in-plant applications, tankers for rail tankers, Tanker Trucks etc. It is an excellent hose for conveying tallow and high aromatic hydrocarbons.

manufacture

Complies with EN 13765 Type 2 & AS 2117 Type 3 Grade 1 & 2.

temperature

Depending on the conveyant -30°C to +80°C.

Special application

Transoil can be supplied with Stainless Steel outer wire also. This hose is called **Transoil S**



Specifications

nominal bore mm	outside dia mm	bend radius mm	pressure nominal psi	bar	weight per meter Kg/m	Std. Prod. Length Meter
25	38	90	150	10	0.90	30
38	52	120	150	10	1.45	30
50	64	150	150	10	1.80	30
65	80	180	150	10	2.50	30
75	92	250	150	10	3.00	30
100	115	350	150	10	4.50	30

Safety factor of 4 : 1

Complies with BS 5842:1980 Standard on demand.

data sheet – CM 014 (01.05.17)

*For further information on Radcoflex
email : sales@radcoflexindia.com
Web : www.radcoflexindia.com*